

Radios
communication without barriers

IM-Series 2.4 GHz

Spread Spectrum OEM Modules European Union and Region 1 Approved



The FreeWave® Technologies family of board level radios provides outstanding performance and versatility in a small footprint that is ideal for OEM applications. The board level radio offers a cost effective solution that allows customers to incorporate wireless communications into a wide variety of applications. With more interface options available, a 9.5-30 VDC operating voltage, a temperature range of -40°C to +75°C, surface mount design, and no additional RF shielding, the OEM board level product has tremendous flexibility for use in applications around the world.



Features:

- **Frequency Hopping**
- **High Speed** – 115.2 Kbps true throughput.
- **Long Range** – 20 mile range, ability to extend through repeaters.
- **Error Free Communications** – 32 bit CRC with automatic retransmission.
- **Industrial Grade Specifications** – 100% tested for full performance from -40°C to +75°C.
- **Repeater** and simultaneous Slave and Repeater function all in a single radio.
- **Improved supply voltage range and power consumption.** Input voltage range is now 9.5-30 VDC at full RF output power. Receive current is less than 100 mA @ 12 VDC. A new sleep mode consumes only 5 mA. A unit in sleep mode will wake up, synchronize with the network, and accept data in less than 150 *milliseconds*.
- **Separate diagnostic serial connector** allows real time local diagnostics and setup menu access.
- **Better diagnostics**, including signal level in dBm and transmit current.
- **RS232 Interface**
- **Noise Immunity** – Superior performance in noise congested environments.
- **Secure** – proprietary spread spectrum technology prevents detection and unauthorized access.
- **100% backward compatible** with every 2.4 GHz FreeWave radio ever shipped.
- **European Union Standards**—programmable to comply with either the EN 300 328-2 or EN 300 440-2 standards.





Communication without barriers

IM-Series 2.4 GHz Spread Spectrum OEM Modules Technical Specifications

Transmitter & Receiver	Transmitter	
	Frequency Range	2.400 - 2.483 GHz
	Output Power	100 mW to 500 mW
	Range, Line of Sight	20 miles with clear line of sight
	Modulation	Spread Spectrum GFSK
	Occupied Bandwidth	230 kHz
	Spreading Method	Frequency Hopping
	Hopping Patterns	15 per band, 105 total, user selectable
	Hopping Channels	75 to 80, user selectable
	Hopping Bands	3, user selectable
	Receiver	
	Sensitivity	-105 dBm for 10 ⁻⁶ BER -107 dBm for 10 ⁻⁴ BER
	Selectivity	20 dB at fc ± 115 kHz 60 dB at fc ± 145 kHz
System Gain	137 dB	

Data Transmission & Power	Data Transmission																					
	Error Detection	32 bit CRC, Retransmit on Error																				
	Data Encryption	Substitution, Dynamic Key																				
	Maximum Throughput	115.2 Kbps																				
	Data Interface	RS232/485/422																				
	Data Connector	10 pin header with locking ramp, 0.1 inch spacing power/data connector. Separate diagnostics connector																				
	Power Requirement																					
	Operating Voltage	9.5-30 VDC																				
	Current Drain	<table border="1"> <thead> <tr> <th>Mode</th> <th>9.5VDC</th> <th>12 VDC</th> <th>30 VDC</th> </tr> </thead> <tbody> <tr> <td>Transmit</td> <td>400 mA</td> <td>325 mA</td> <td>150 mA</td> </tr> <tr> <td>Receive</td> <td>130 mA</td> <td>115mA</td> <td>60 mA</td> </tr> <tr> <td>Idle</td> <td>37 mA</td> <td>30 mA</td> <td>13 mA</td> </tr> <tr> <td>Sleep</td> <td>8 mA</td> <td>5 mA</td> <td>2 mA</td> </tr> </tbody> </table>	Mode	9.5VDC	12 VDC	30 VDC	Transmit	400 mA	325 mA	150 mA	Receive	130 mA	115mA	60 mA	Idle	37 mA	30 mA	13 mA	Sleep	8 mA	5 mA	2 mA
		Mode	9.5VDC	12 VDC	30 VDC																	
		Transmit	400 mA	325 mA	150 mA																	
		Receive	130 mA	115mA	60 mA																	
		Idle	37 mA	30 mA	13 mA																	
Sleep	8 mA	5 mA	2 mA																			

General	General Information	
	Operating Temperature Range	-40°C to +75°C 100% full performance tested
	Dimension	127 mm L x 60.96 mm W x 15.49 mm H
	Weight	74.4 grams
	External Antenna Connector	SMA– Military and Export Only Reverse SMA– Professional Installation only.
	Humidity	0 to 95% non-condensing

Specifications may change at any time without notice
© 2005 FreeWave Technologies, Inc.