

VXR-7000

VHF/UHF Desktop Repeater



■ FREQUENCY RANGE*:

VHF : 136-150 MHz (A) or 150-174 MHz (C)

UHF : 400-430 MHz (A) or 450-480 MHz (D) or 480-512 MHz (F)

■ 16 CHANNEL SYNTHESIZED

■ 10-50 WATTS POWER OUTPUT (100 % DUTY)

■ 12.5 / 25 kHz BANDWIDTH PROG 16 TONES / CODES)

■ ANI / ENI ID DISPLAY

■ CW TRANSMITTER ID

■ TIME-OUT TIMER, HANG TIMER, GUARD TIMER

(DEALER PROGRAMMED)

■ BCLO,BTLO

■ SELECTABLE REPEATER MODE OR BASE TRANSCIVER MODE

■ SELECTABLE LOCAL MODE OR REMOTE MODE

■ AC POWER SUPPLY VOLTAGE SELECTION
(115 / 230 VAC < ±10 % >)

■ AUTOMATIC DC POWER SUPPLY BACKUP

■ OPTIONAL INTERNAL DUPLEXER

■ PC PROGRAMMING

■ ACC CONNECTOR PORT & LINE INTERFACE PORT

■ VX-TRUNK OPERATION (OPTIONAL)



With a long list of built in features, the VXR-7000 Series Base / Repeater Station sets the standard for mid-power, continuous duty base station and repeater applications.

Designed with long term reliability in mind. The VXR-7000 Series offers unmatched features and performance for all segments of industry and Public Safety. Whether used as a base station, with its attractive housing and user friendly controls, or as a remote repeater, in the most demanding environments, the VXR-7000 series will provide years of reliable service.

Manufactured utilizing the most advanced state-of-the-art computer aided design and manufacturing processes. The VXR-7000 series sets the standard for rugged environment applications now.

Specifications

General Specifications	
Frequency Range	VXR-7000 VHF : 136-150 MHz(A) or 146-174 MHz(C) VXR-7000 UHF : 400-430 MHz(A) or 440-470 MHz(B) or 450-490 MHz(D) or 480-512 MHz(F)
Number of Channels	16 Channels
Channel Spacing	12.5 / 25 kHz
Frequency Stability	±2.5 ppm
Antenna Impedance	50 (N-Type)
Tx Activation System	Carrier-operated, CTCSS tone operated, DCS operated, or remote control
Power Requirements	115 / 230 V AC ±10 %, 50 / 60 Hz or 13.8 VDC
Ambient Temperature Range	-22° F to +140° F (-30° C - +60° C)
Dimensions (w/o knobs)	4.5"(H) X 12.8"(W) X 15.4"(D)(115 X 325 X 391.5 mm)
Weight (approx.)	22 lbs. (10 kg)

Receiver Specifications	
Receiver type	Double-conversion Superheterodyne
Sensitivity	0.35 µV for 12 dB SINAD, 0.45 µV for 20 dB NQ
Selectivity	75 dB
Intermodulation	75 dB
Spurious & Image Rejection	80 dB
Audio Output	4 W @ 4

Transmitter Specifications	
RF Output	10-50 W (Adjustable)
Duty Cycle	100 %
Maximum Deviation	±5.0 kHz (25 kHz spacing), ±2.5 kHz (12.5 kHz spacing)
Modulation Type	16K0F3E / 11K0F3E
Audio Distortion	Less than 2.5 % @ 1 kHz
Spurious Emissions	Better than 75 dB below carrier

*Specifications subject to change without notice or obligation.

Measurements per EIA standards unless noted above. Specifications subject to change without notice or obligation. Various accessories listed may not be available in some countries.




- ① POWER Switch
- ② LED Indicators
- ③ MIC Jack
- ④ BASE/REPEATER Switch
- ⑤ LOCAL/REMOTE Switch
- ⑥ MONITOR Switch
- ⑦ ACCESSORY Switch
- ⑧ VOL Knob
- ⑨ SQL Knob
- ⑩ Channel Selector Buttons
- ⑪ Channel Indicator
- ⑫ ANI Display
- ⑬ TX/BUSY Indicator
- ⑭ ANI RESET Button

Accessories & Options



- CE-27 Programming Software
- CT-68 Antenna Cable w / Mount screws (for the Antenna Duplexer)
- VTS-300 VX-Trunk Controller

Rear Panel



- ① EXT SP Jack
- ② TX Antenna Jack
- ③ RX Antenna Jack
- ④ ACC Jack
- ⑤ LINE Jack
- ⑥ GND Terminal
- ⑦ AC Jack
- ⑧ BATT Terminal

Vertex Standard
VERTEX STANDARD CO., LTD.

4-8-8 Nakameguro, Meguro-ku, Tokyo 153-8644, Japan



VERTEX STANDARD

US Headquarters
 10900 Walker Street, Cypress, CA 90630, U.S.A.

YAESU (VERTEX STANDARD) UK LTD.

Unit 12, Sun Valley Business Park, Winnall Close
 Winchester, Hampshire, SO23 0LB, U.K.

VERTEX STANDARD HK LTD.

Unit 5, 20/F., Seaview Centre, 139-141 Hoi Bun Road,
 Kwun Tong, Kowloon, Hong Kong

VSPECTRA
 Expanding horizons

Authorised Distributors for South West Asia :

Thunderbird Industries (India) Pvt. Ltd.

A-16, Mohan Cooperative Industrial Estate Ltd., New Delhi-110044, India
 Tel.: +91-11-51679272 / 73 Fax : +91-11-51679274
 Email : sales@vspectra.com

PBR7000041